



(12) **United States Patent**
McGregor

(10) **Patent No.:** **US 9,408,463 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **UNDERMOUNT DRAWER SLIDE POSITION
ADJUSTMENT APPARATUS AND METHOD
OF USE**

(71) Applicant: **Hardware Resources, Inc.**, Bossier
City, LA (US)

(72) Inventor: **Dennis McGregor**, Bossier City, LA
(US)

(73) Assignee: **HARDWARE RESOURCES, INC.**,
Bossier City, LA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/821,979**

(22) Filed: **Aug. 10, 2015**

(65) **Prior Publication Data**
US 2015/0342347 A1 Dec. 3, 2015

Related U.S. Application Data

(63) Continuation of application No. 14/088,053, filed on
Nov. 22, 2013, now Pat. No. 9,101,213.

(51) **Int. Cl.**
A47B 88/04 (2006.01)

(52) **U.S. Cl.**
CPC **A47B 88/0422** (2013.01); **A47B 88/0407**
(2013.01); **A47B 2088/0433** (2013.01); **Y10T**
29/4984 (2015.01)

(58) **Field of Classification Search**
CPC A47B 88/0407; A47B 88/0418; A47B
88/0422; A47B 88/044; A47B 2210/0054
USPC 312/334.4, 334.5, 348.4, 333
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

139,228 A * 5/1873 Arnold F16K 31/05
16/210
808,927 A * 1/1906 Hunn F16K 31/05
74/89.45
4,441,773 A * 4/1984 Leiper A47B 88/14
312/330.1
5,306,080 A * 4/1994 Lautenschlager A47B 88/044
312/334.5
5,580,139 A * 12/1996 Grabher A47B 88/0422
312/333
6,027,193 A * 2/2000 Domenig A47B 88/0462
312/334.14

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0761132 3/1997
EP 1440631 7/2007

(Continued)

Primary Examiner — Daniel Rohrhoff

(74) *Attorney, Agent, or Firm* — Schultz & Associates, P.C.

(57) **ABSTRACT**

An undermount drawer slide mounting clip releasably
attaches a drawer to a drawer rail assembly mounted in a
cabinet carcass. The apparatus is capable of effecting posi-
tional adjustments of the drawer in three directions without
removing the drawer from the cabinet carcass. The apparatus
is comprised of a body slidably engaged with a bonnet. A
trigger pivotally connected between the body and the bonnet.
A spring loaded catch slidable within the bonnet and acted on
by the trigger to releasably attach the apparatus to a drawer
rail assembly. A threaded spindle rotates within the base and
adjusts the horizontal position of the drawer. A ramp adjust-
ably connected to the base adjusts the vertical position of the
drawer. A plunger extends from a housing connected to the
body and is adjacent the drawer rail assembly. A lever pivot-
able within the housing moves the plunger and adjusts the
depth of the drawer.

18 Claims, 6 Drawing Sheets

